


ITEM	QTY. -041	PART NUMBER	DESCRIPTION
1	X	D4434-041	FWD BRACKET ASSEMBLY
2	1	D4434-043	FWD INBOARD BRACKET ASSEMBLY
3	1	D4434-045	FWD OUTBOARD BRACKET ASSEMBLY
4	4	AN525-832R7	SCREW




D4434-041 FWD BRACKET ASSEMBLY

- NOTES:
- 1) MATERIAL: N/A
 - 2) FINISH: N/A
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
 - 7) WEIGHT: 1.38 lbs
 - 8) TORQUE SCREW TO 12-15 (in-lb)

RELEASED
2014 -03- 31

C	ADD & CHANGE DIM TO 2 DEC PL (ZN C6-9, C7-9); REVISE D4434-045/-5/-5F (ZN B5-4, A5-10, B5-11); ADD ADHESIVE TO D4434-045 BOM (ZN D4-4)	RF	14.03.06
B	RE-DESIGN D4434-9/-9F (ZN B5-14, A5-15)	RF	12.02.22
A	NEW ISSUE	RF	12.01.17
REV.	DESCRIPTION	BY	DATE
DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	DC	DRAWING NO.	REV. C
MFG. APPR.	DD	D4434	SHEET 1 OF 15
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	COVER ASSEMBLY	NTS
DATE	14.03.06	COPYRIGHT © 2012 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	



ITEM	QTY -043	PART NUMBER	DESCRIPTION
1	X	D4434-043	FWD INBOARD BRACKET ASSEMBLY
2	1	D4434-1	BRACKET
3	1	D4434-9	BRACKET
4	1	D4435-041	BRACKET ASSEMBLY
5	1	D4440-1	GROMMET
6	1	D4441-1-017	RUBBER SEAL
7	1	D4441-1-025	RUBBER SEAL
8	1	D4441-1-225	RUBBER SEAL
9	3	AN525-832R6	SCREW
10	12	MS20426AD3-2	RIVET
11	2	MS20426AD3-3	RIVET
12	5	MS20470AD4-3	RIVET
13	7	MS21075L08	NUT PLATE
14	A/R	3M 1300/1300L	ADHESIVE

NOTES:


- 1) MATERIAL: N/A
- 2) FINISH: POWDER COAT "BLACK SANDTEX" (4.3.5.7) PER DART QSI 005 4.3
MASK NUT PLATE HOLES
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 1.00 lbs
- 8) INSTALL RUBBER SEAL TO EDGE OF PART AFTER POWDER COAT USING 3M 1300/1300L ADHESIVE
ENSURE BRACKET IS COMPLETELY INSERTED INTO GROOVE OF RUBBER SEAL
IT IS ACCEPTABLE TO NOTCH THE SEAL AS REQUIRED TO PREVENT IT FROM BUCKLING
- 9) TORQUE SCREW TO 12-15 (in-lb)

D4434-043 FWD INBOARD BRACKET ASSEMBLY

RELEASED
2014-03-31

APPROVED

DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	DC	DRAWING NO. D4434	REV. C
MFG. APPR.	DD	SHEET 2 OF 15	
APPROVED	HS	TITLE COVER ASSEMBLY	SCALE NTS
DE APPR.	DS	COPYRIGHT © 2012 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	
DATE	14.03.06		



NOTES:

- 1) MATERIAL: N/A
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 1.00 lbs
- 8) TRANSFER $\varnothing 0.129$ HOLES THRU 5 PLACES FROM D4434-9 TO D4434-1
- 9) TRANSFER $\varnothing 0.098$ HOLES THRU 2 PLACES FROM D4434-9 TO D4434-1
- 10) CSK $\varnothing 0.179 \times 100^\circ$ ON THIS SIDE 2 PLACES
- 11) TRANSFER $\varnothing 0.177$ HOLE THRU FROM D4434-9 TO D4434-1


D4434-043 FWD INBOARD BRACKET ASSEMBLY AUXILIARY VIEW

RELEASED
2014-03-31

APPROVED

DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	DC	DRAWING NO. D4434	REV. C
MFG. APPR.	DD	SHEET 3 OF 15	
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	COVER ASSEMBLY	NTS
DATE	14.03.06	<small>COPYRIGHT © 2012 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	

ITEM	QTY -045	PART NUMBER	DESCRIPTION
1	X	D4434-045	FWD OUTBOARD BRACKET ASSEMBLY
2	1	D4434-3	BRACKET
3	1	D4434-5	BRACKET
4	1	D4441-1-060	RUBBER SEAL
5	6	MS20426AD4-4	RIVET
6	A/R	3M 1300/1300L	ADHESIVE



D4434-045 FWD OUTBOARD BRACKET ASSEMBLY

NOTES:


- 1) MATERIAL: N/A
- 2) FINISH: POWDER COAT "BLACK SANDTEX" (4.3.5.7) PER DART QSI 005 4.3 MASK NUT PLATE HOLES
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 0.38 lbs
- 8) INSTALL RUBBER SEAL TO EDGE OF PART AFTER POWDER COAT USING 3M 1300/1300L ADHESIVE ENSURE BRACKET IS COMPLETELY INSERTED INTO GROOVE OF RUBBER SEAL IT IS ACCEPTABLE TO NOTCH THE SEAL AS REQUIRED TO PREVENT IT FROM BUCKLING
- 9) TRANSFER $\phi 0.129$ HOLE 6 PLACES AND CSK TO $\phi 0.225 \times 100^\circ$

RELEASED
2014 -03- 31

APPROVED

DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	DC	DRAWING NO. D4434	REV. C
MFG. APPR.	DD	SHEET 4 OF 15	
APPROVED	HS	TITLE COVER ASSEMBLY	SCALE NTS
DE APPR.	DS	COPYRIGHT © 2012 BY DART AEROSPACE LTD	
DATE	14.03.06	THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

ITEM	QTY -047	PART NUMBER	DESCRIPTION
1	X	D4434-047	COVER ASSEMBLY
2	1	D4434-7	BRACKET
3	2	MS20470AD4-3	RIVET




D4434-047 COVER ASSEMBLY

RELEASED
2014-03-31

- NOTES:
- 1) MATERIAL: N/A
 - 2) FINISH: POWDER COAT "BLACK SANDTEX" (4.3.5.7) PER DART QSI 005 4.3
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
 - 7) WEIGHT: 0.26 lbs

APPROVED	DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
	DRAWN	RF		
	CHECKED	DC	DRAWING NO. D4434	REV. C
	MFG. APPR.	DD	SHEET 5 OF 15	
	APPROVED	HS	TITLE	SCALE
	DE APPR.	DS	COVER ASSEMBLY	NTS
DATE 14.03.06			COPYRIGHT © 2012 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	



D4434-1 BRACKET

DETAIL B C8-6
SCALE 2X

RELEASED
2014-03-31

- NOTES:**
- 1) MATERIAL: MAKE FROM D4434-1F FLAT PATTERN
 - 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: N/A
 - 7) WEIGHT: 0.70 lbs

APPROVED

DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	DC	DRAWING NO. D4434	REV. C
MFG. APPR.	DD	SHEET 6 OF 15	
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	COVER ASSEMBLY	NTS
DATE	14.03.06	COPYRIGHT © 2012 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	


8 7 6 5 4 3 2 1

D


C

B

A



DETAIL C
SCALE 2X B6-7



D4434-1F FLAT PATTERN


RELEASED
2014-03-31
[Signature]

NOTES:

- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET 0.040 THICK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027
OR ASTM B209
REF DART SPEC. M6061T6S.040
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 0.70 lbs

APPROVED


DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	DC	DRAWING NO. D4434	REV. C
MFG. APPR.	DD	SHEET 7 OF 15	
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	COVER ASSEMBLY	NTS
DATE	14.03.06	COPYRIGHT © 2012 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	



D4434-3 BRACKET

- NOTES:
- 1) MATERIAL: MAKE FROM D4434-3F FLAT PATTERN
 - 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: N/A
 - 7) WEIGHT: 0.14 lbs

RELEASED
2014-03-31
MA



D4434-3F FLAT PATTERN


RELEASED
2014-03-31
WMD


NOTES:

- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET 0.040 THICK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027
OR ASTM B209
REF DART SPEC. M6061T6S.040
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 0.14 lbs

APPROVED

DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	DC	DRAWING NO.	REV. C
MFG. APPR.	DD	D4434	SHEET 9 OF 15
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	COVER ASSEMBLY	NTS
DATE	14.03.06	COPYRIGHT © 2012 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	





D4434-5F FLAT PATTERN


NOTES:

- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET 0.040 THICK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027
OR ASTM B209
REF DART SPEC. M6061T6S.040
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 0.20 lbs

RELEASED
2014 -03- 31

APPROVED

DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	DC	DRAWING NO.	REV. C
MFG. APPR.	DD	D4434	SHEET 11 OF 15
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	COVER ASSEMBLY	NTS
DATE	14.03.06	<small>COPYRIGHT © 2012 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	




D4434-7 BRACKET

- NOTES:**
- 1) MATERIAL: MAKE FROM D4434-7F FLAT PATTERN
 - 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: N/A
 - 7) WEIGHT: 0.26 lbs
 - 8) TRANSFER $\varnothing 0.129$ HOLE THRU 2 PLACES

RELEASED
2014-03-31

APPROVED	DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
	DRAWN	RF		
	CHECKED	DC	DRAWING NO.	REV. C
	MFG. APPR.	DD	D4434	SHEET 12 OF 15
	APPROVED	HS	TITLE	SCALE
	DE APPR.	DS	COVER ASSEMBLY	NTS
DATE 14.03.06			COPYRIGHT © 2012 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	




D4434-7F FLAT PATTERN

RELEASED
2014-03-31
W

- NOTES:**
1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET 0.040 THICK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027
OR ASTM B209
REF DART SPEC. M6061T6S.040
2) FINISH: N/A
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: N/A
7) WEIGHT: 0.26 lbs

APPROVED	DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
	DRAWN	RF		
	CHECKED	DC	DRAWING NO.	REV. C
	MFG. APPR.	DD	D4434	SHEET 13 OF 15
	APPROVED	HS	TITLE	SCALE
	DE APPR.	DS	COVER ASSEMBLY	NTS
DATE		14.03.06	COPYRIGHT © 2012 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	



D4434-9 BRACKET


NOTES:

- 1) MATERIAL: MAKE FROM D4434-9F FLAT PATTERN
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 0.10 lbs

APPROVED

DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA
DRAWN	RF	
CHECKED	DC	DRAWING NO. REV. C
MFG. APPR.	DD	D4434 SHEET 14 OF 15
APPROVED	HS	TITLE SCALE
DE APPR.	DS	COVER ASSEMBLY NTS
DATE	14.03.06	COPYRIGHT © 2012 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

RELEASED
2014-03-31



D4434-9F FLAT PATTERN

APPROVED	DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
	DRAWN	RF		
	CHECKED	DC	DRAWING NO.	REV. C
	MFG. APPR.	DD	D4434	SHEET 15 OF 15
	APPROVED	HS	TITLE	SCALE
	DE APPR.	DS	COVER ASSEMBLY	NTS
DATE		14.03.06	COPYRIGHT © 2012 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	